

Models 24A/34A

PERFORMANCE

	Full Scale Pressure Range	0-3 thru 5000 PSIG (PSIG FOR >500 PSI) (0.2 thru 345 bar) 0-15 thru 0-5000 PSIA (0-1.0 thru 0-345 bar) 0-5 thru 0-15 PSIV (0-.34 thru 1.03 BarV)
	Nonlinearity (Best Fit Straight Line)	≤±0.25% FSO
	Hysteresis & Repeatability	≤±0.10% FSO each
Full Scale Output (FSO)	Model 24A.....	5 Vdc at 70°F (21°C) ±1.0% FSO standard
	Model 34A.....	16 mA at 70°F (21°C) ±1.0% FSO
	Zero and Span Balance	± 1% FSO
	Resolution	Infinite
Temperature Shift	Long Term Stability	≤±0.3% FSO per 6 months
	Compensated Temperature.....	70°F to 170°F (21°C to 77°C)
	Operating Temperature.....	-40°F to 250°F (-40°C to 121°C) - process -40°F to 185°F (-40°C to 85°C) - ambient
	Storage Temperature Limits.....	-40°F to 250°F (-40°C to 121°C)
	Temperature Effect on Zero	≤±2.0% FSO per 100°F
	Temperature Effect on Span	≤±2.0% FSO per 100°F

ELECTRICAL

Supply Voltage	Model 24A	8 to 30 Vdc at 3.5 mA nominal, 5 mA max (12 to 30 Vdc for 10 Vdc output option)
	Model 34A	8 to 30 Vdc
Output Signal	Model 24A	0 - 5 Vdc standard (see options)
	Model 34A	4 to 20 mA
	Circuit Protection	Reverse polarity protected. Output may be short circuited indefinitely. Over voltage protection to 1000 volts according to EN61000-4-5
	Insulation Resistance	≤ 5 nS to case ground
	Response Time.....	<2 mSec to reach 90% of full scale
	RFI/EMI Suppression.....	CE EMC compliant per IEC EN 61326. CE marked.
	Electrical Connection	Bendix PT02E-10-6P, mates PT06E-10-6S (SR)

Model 24A

Pin A	+Power
Pin B	-Power
Pin C	+Signal
Pin D	-Signal
Pin E	No Connection
Pin F	No Connection
Shell	Ground

Model 34A

	+Power/Signal
	-Power/Signal
	No Connection
	No Connection
	No connection
	No connection
	Ground

MATERIALS OF CONSTRUCTION

Wetted Parts	316 Stainless Steel
Housing.....	304L Stainless Steel
Weight	10 oz (283 g)
Identification	Permanently marked on body of unit

ACCESSORIES

- Direct Mount Digital Indicator/Power Supply
- Mating Electrical Assembly
- Ruggedized Connectors & Cable Assemblies

Models 24A / 34A

MECHANICAL

Pressure Connection	Pressure Connection.....	1/4" - 18 NPT female
Proof Pressure	≤500 PSI (35 bar).....	3 times range or 1,200 PSI (80 bar) max
	>500 PSI (35 bar).....	3 times range or 9,000 PSI (620 bar) max
Burst Pressure	≤500 PSI (35 bar).....	5 times range or 2,400 PSI (170 bar) max
	>500 PSI (35 bar).....	5 times range or 10,000 PSI (700 bar) max
Pressure Cavity Volume	≤500 PSI (35 bar).....	1.5 ml
	>500 PSI (35 bar).....	1.5 ml
	Mounting.....	May be supported by process piping

OPTIONS

BF.....	(K)PTIH-10-6P
BG.....	DIN 43650
BL.....	WK6-32S
BN.....	(K)PTIH-8-4P
BQ.....	(K)PTO2H-10-6P
BR.....	CF3102E-14S-6P
DA.....	Isolated Shunt Calibration Circuit
DC.....	Extended Compensated Temperature Range (Cold) -40°F to 170°F (-40°C to 77°C)
DG.....	Improved temperature compensation (≤±1.0%FSO per 100°F, zero and span shift)
DH.....	Special ranging
DK.....	Special calibration setting
DM.....	Modified full scale output
DN.....	Improved linearity (±0.15% FSO)
DQ.....	Cleaning for oxygen service
EA.....	Special calibration run
ED.....	Extra improved linearity (±0.10% FSO)
EH.....	Extended Compensated Temperature Range (Hot) +70°F to 185°F (21°C to 85°C)
LV.....	Externally powered, Optically Isolated Shunt Cal
NH.....	Customer specified identification
NW.....	External zero adjustment
PW.....	1/8 DIN digital indicator
TH.....	External zero and span adjustment
TU.....	Compound & Bi-directional special ranges
TW.....	GOST-R approval
Y.....	Multiple pressure ports available. Consult factory
ZU.....	Direct cable (175°F Max Temp) (79°C)

Note: Application of some available options may affect standard performance. Consult your Viatran representative for details.

